


TigerTurf Football 22/170 PP

Product Data Specification

Product Name:	Football 22/170 PP
Main Application:	Football
Colours:	Forest, Olive, Brick, Blue, Grey



Product Description: A medium pile (22mm above the backing), sand filled, fibrillated football surface.

It is our standard yarn that has been New Zealand's number one since synthetic grass was introduced. It is a versatile yarn that is suitable for football of all types. The yarn used in this product is equal in performance to any fibrillated yarn in Australasia. Available in numerous colour combinations to suit your requirements including Olive, Brick, Forest, Blue and Grey. Also featuring a uniquely formulated latex backing, designed to last in continuous wet conditions, and provide greater seam strength when used in conjunction with approved adhesives. Football 22/170 PP is UV stabilised to meet the extremes that the New Zealand and Australian climate presents. Football 22/170 PP is warranted against UV breakdown for five (5) years.

YARN CHARACTERISTICS

Heavy Metal Free, UV resistant Type: Fibrillated Homo-polymer Composition/Structure: Bonar 888Tex Fibrillated

BACKING CHARACTERISTICS

PRIMARY BACKING 1

Composition/Structure: 100 % woven polypropylene, UV resistant

Weight: 120g/sqm Colour: Black

SECONDARY BACKING

"SUPERBOND" latex compound Compound Base:

Styrene - butadiene basis

Colour: Black Coating Weight: 600g/sqm

PARTICULATE INFILL

Siliceous, round, washed and dried Sand Type:

Sand Size/Range <0.2 mm and >1.0 mm

Infill Weight: 24 kg/sqm Infill Height: 20 mm

TUFT CHARACTERISTICS

Pile Weight: 777g/sqm Pile Height: 22 mm Total Pile Length: 49 mm # Stitches: 170 per metre # Knots: 17,850 # Piles: 35,700 Machine Gauge:

MANUFACTURED ROLLS

Width (useable): 3.71 metres Length: Various

Line Colours: White, Yellow Line Widths: 50 mm, 100mm

Roll Diameter: 600 mm (based on 36 metres

roll)

TOTAL PRODUCT

1377 g/sqm WEIGHT:

Installation Advice: This product is to be directly laid onto a stabilised sub-base such as TigerBond, Asphalt or Con-

crete. It is also possible to lay the surface onto a Compacted Metal base although it is important to note that this is not the ideal sub-base. All seams should be glued with an appropriate adhesive. Carpet to be infilled with sand, as specified above and then groomed before play. For further

information on the installation of this surface please contact TigerTurf.

Maintenance Advice: This product will perform to its optimum and last longer with regular maintenance.

Warranty: TigerTurf offer a five year warranty on this product, which is available upon request.

All measurements are within + or - 10% TigerTurf reserves the right to modify this information.

Olympic Venture - All Sports Builder

c/o Sin Hong Moh Sdn. Bhd.

601-L, Jalan Air Itam, 11500 Penang, Malaysia Tel: 604-828 0649, 828-3216 Fax: 604-828 2726

Email: Richard@OlympicVenture.com H/P: 6016-497 8293 / 6012-429 5239 (Richard)

c/o Sin Hong Moh S/B 601-L, Jalan Air Itam 11500 Penang, Malaysia el: 604-828 0649

604-828 2726 6016-497 8293 / 6012-429 5239

RICHARD CHEAH

OlympicVenture.com